

Classic Fix 65


- IP44
- Class III
- Ceiling Recessed
- Acoustic Proof
- Anti glare hazard UGR<17
- RG1 | Blue light
- 65mm
- Altamente riciclabile
Highly recyclable
- FSC
Package



9Watt Deep Fixed Downlight

Code	System Power	LED Power	Lumens(at 3000K)	CRI	Lifetime (Ta 25°C)
DL6042	11W	250mA 36V	900lm	93/97	50.000h L80B20

Finish	LED CCT	Beam	Key Information	
Powder Coat	2700K	15°	Material	Aluminium
Liquid Paint	3000K	24°	Mounting	Ceiling Recessed
Anodize	4000K	36°	Gear	This product is supplied without gear.
Plate	D2W	50°	Warranty	5 Year
	TW			



Light Distribution for 3000K

medium 30°			wide 49°		
h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)
1	1843	o0.55	1	1078	o0.91
2	460.6	o1.09	2	269.6	o1.83
3	204.7	o1.64	3	119.8	o2.74
4	115.2	o2.29	4	67.39	o3.65
5	73.70	o2.74	5	43.13	o4.56

Accessories

- 2 | Glass Diffuser
- 2 | Honeycomb Louvre