

Semi OwI 40

IP44

Class III

Ceiling Recessed

Acoustic Proof

Anti glare hazard
UGR<19

RG1 | Blue light

38-40mm

Altamente riciclabile
Highly recyclable


FSC
Package



4.3Watt Round Semi Recessed Downlight

Code	System Power	LED Power	Lumens(at 3000K)	CRI	Lifetime (Ta 25°C)
DL3298	5.4W	120mA 36V	250lm	93/97	50.000h L90B10

Finish	LED CCT	Beam	Key Information	
101 Textured White	2700K	15°	Material	Aluminium
102 Textured Black	3000K	24°	Mounting	Ceiling Recessed
406 Rose Gold	4000K	36°	Gear	This product is supplied without gear.
			Warranty	5 Year



Light Distribution for 3000K

spot 15°			medium 20°			wide 36°		
h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)
1	1972	ø0.27	1	1985	ø0.35	1	835.0	ø0.63
2	492.9	ø0.54	2	496.3	ø0.70	2	208.7	ø1.27
3	219.1	ø0.82	3	220.6	ø1.06	3	92.77	ø1.91
4	123.2	ø1.09	4	124.1	ø1.41	4	52.19	ø2.55
5	78.87	ø1.36	5	79.41	ø1.77	5	33.40	ø3.19