

Cube Compact 280

IP44

Class III

Ceiling Recessed

Anti glare hazard
UGR<19

RG1 | Blue light

280x100mm

Altamente riciclabile
Highly recyclable


FSC
Package



25.3Watt Tiltable Rectangular Downlight

Code	System Power	LED Power	Lumens(at 3000K)	CRI	Lifetime (Ta 25°C)
DL3350	28.9W	700mA 36V	1850lm	93/97	50.000h L90B10

Finish	LED CCT	Beam	Key Information	
101 Textured White	2700K	24°	Material	Aluminium
102 Textured Black	3000K	36°	Mounting	Ceiling Recessed
	4000K	45°	Gear	This product is supplied without gear.
	D2W		Warranty	5 Year
	TW			



Light Distribution for 3000K

spot 24°			medium 36°			wide 60°		
h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)
1	7878	ø0.46	1	4358	ø0.64	1	2847	ø0.95
2	1969	ø0.91	2	1089	ø1.29	2	711.7	ø1.91
3	875.3	ø1.36	3	484.2	ø1.93	3	316.3	ø2.86
4	492.4	ø1.82	4	272.4	ø2.58	4	177.9	ø3.81
5	315.1	ø2.27	5	174.3	ø3.22	5	113.9	ø4.77