

Gyro Semi 15


-  IP65
-  Class III
-  Ceiling Recessed
-  Acoustic Proof
-  Anti glare hazard UGR<19
-  RG1 | Blue light
-  70mm
-  Altamente riciclabile Highly recyclable
-  FSC Package



9Watt Waterproof Gyro Tiltable Downlight with Adaptor Ring


Code	System Power	LED Power	Lumens(at 3000K)	CRI	Lifetime (Ta 25°C)
DL3705	11W	250mA 36V	700lm	93/97	50.000h L90B10

Finish	LED CCT	Beam	Key Information	
101 Textured White	2700K	24°	Material	Aluminium
102 Textured Black	3000K	36°	Mounting	Ceiling Recessed
	4000K	50°	Gear	This product is supplied without gear.
			Warranty	5 Year





Light Distribution for 3000K

spot 15°			wide 60°		
h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)
1	3683	ø0.33	1	783.0	ø0.87
2	920.7	ø0.67	2	195.7	ø1.74
3	409.2	ø1.00	3	87.00	ø2.61
4	230.2	ø1.34	4	48.94	ø3.48
5	147.3	ø1.67	5	31.32	ø4.35



Accessories

- 2 |  Glass Diffuser
- 2 |  Honeycomb Louvre