

# Gyro Semi 40



-  IP65
-  Class III
-  Ceiling Recessed
-  Acoustic Proof
-  Anti glare hazard UGR<19
-  RG1 | Blue light
-  70mm
-  Altamente riciclabile Highly recyclable
-  FSC Package



## 9Watt Waterproof Gyro Tiltable Downlight with Adaptor Ring

Code	System Power	LED Power	Lumens(at 3000K)	CRI	Lifetime (Ta 25°C)
DL3705	11W	250mA 36V	700lm	93/97	50.000h L90B10


Finish	LED CCT	Beam	Key Information	
101 Textured White	2700K	24°	Material	Aluminium
102 Textured Black	3000K	36°	Mounting	Ceiling Recessed
	4000K	50°	Gear	This product is supplied without gear.
			Warranty	5 Year



### Light Distribution for 2700K

spot 15°			wide 60°		
h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)
1	3683	o0.33	1	783.0	o0.87
2	920.7	o0.67	2	195.7	o1.74
3	409.2	o1.00	3	87.00	o2.61
4	230.2	o1.34	4	48.94	o3.48
5	147.3	o1.67	5	31.32	o4.35

### Accessories

- 2  Glass Diffuser
- 2  Honeycomb Louvre