






Gyro Square 90


-  IP65
-  Class III
-  Ceiling Recessed
-  Acoustic Proof
-  Anti glare hazard UGR<19
-  RG1 | Blue light
-  70mm
-  Altamente riciclabile Highly recyclable
-  FSC Package



9Watt Waterproof Gyro Tiltable Downlight with Adaptor Ring

| Code | System Power | LED Power | Lumens(at 3000K) | CRI | Lifetime (Ta 25°C) |
|--------|--------------|-----------|------------------|-------|--------------------|
| DL3705 | 11W | 250mA 36V | 700lm | 93/97 | 50.000h L90B10 |



| Finish | LED CCT | Beam | Key Information | |
|--------------------|---------|------|-----------------|--|
| 101 Textured White | 2700K | 24° | Material | Aluminium |
| 102 Textured Black | 3000K | 36° | Mounting | Ceiling Recessed |
| | 4000K | 50° | Gear | This product is supplied without gear. |
| | | | Warranty | 5 Year |



Light Distribution for 3000K

| spot 15° | | | wide 60° | | |
|----------|-------|-------|----------|-------|-------|
| h(m) | E(lx) | o(m) | h(m) | E(lx) | o(m) |
| 1 | 3683 | o0.33 | 1 | 783.0 | o0.87 |
| 2 | 920.7 | o0.67 | 2 | 195.7 | o1.74 |
| 3 | 409.2 | o1.00 | 3 | 87.00 | o2.61 |
| 4 | 230.2 | o1.34 | 4 | 48.94 | o3.48 |
| 5 | 147.3 | o1.67 | 5 | 31.32 | o4.35 |

Accessories

- 2 |  Glass Diffuser
- 2 |  Honeycomb Louvre