

# Gyro Rectangle 175

-  IP65
-  Class III
-  Ceiling Recessed
-  Acoustic Proof
-  Anti glare hazard UGR<19
-  RG1 | Blue light
-  70mm²
-  Altamente riciclabile Highly recyclable
-  FSC Package




## 9Watt Waterproof Gyro Tiltable Downlight with Adaptor Ring(2 Units)

Code	System Power	LED Power	Lumens(at 3000K)	CRI	Lifetime (Ta 25°C)
DL3705	11W	250mA 36V	700lm	93/97	50.000h L90B10

Finish	LED CCT	Beam
<span style="border: 1px solid black; padding: 2px;">101</span> Textured White	<span style="display: inline-block; width: 10px; height: 10px; background-color: orange;"></span> 2700K	<span style="display: inline-block; width: 10px; height: 10px; background-color: yellow;"></span> 24°
<span style="border: 1px solid black; padding: 2px;">102</span> Textured Black	<span style="display: inline-block; width: 10px; height: 10px; background-color: orange;"></span> 3000K	<span style="display: inline-block; width: 10px; height: 10px; background-color: yellow;"></span> 36°
	<span style="display: inline-block; width: 10px; height: 10px; background-color: orange;"></span> 4000K	<span style="display: inline-block; width: 10px; height: 10px; background-color: yellow;"></span> 50°



Key Information	
Material	Aluminium
Mounting	Ceiling Recessed
Gear	This product is supplied without gear.
Warranty	5 Year



### Light Distribution for 3000K

spot 15°			wide 60°		
h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)
1	6629	o0.34	1	1174.5	o0.97
2	1657	o0.68	2	293.5	o1.84
3	736.5	o1.01	3	130.5	o2.71
4	414.3	o1.35	4	73.41	o3.58
5	265.1	o1.68	5	48.46	o4.45

### Accessories

- 2  Glass Diffuser
- 2  Honeycomb Louvre