

Gyro Rectangle 260

-  IP65
-  Class III
-  Ceiling Recessed
-  Acoustic Proof
-  Anti glare hazard UGR<19
-  RG1 | Blue light
-  70mm*3
-  Altamente riciclabile Highly recyclable
-  FSC Package




9Watt Waterproof Gyro Tiltable Downlight with Adaptor Ring(3 Units)

Code	System Power	LED Power	Lumens(at 3000K)	CRI	Lifetime (Ta 25°C)
DL3705	11W	250mA 36V	700lm	93/97	50.000h L90B10

Finish	LED CCT	Beam
101 Textured White	2700K	24°
102 Textured Black	3000K	36°
	4000K	50°



Key Information	
Material	Aluminium
Mounting	Ceiling Recessed
Gear	This product is supplied without gear.
Warranty	5 Year



Light Distribution for 3000K

spot 15°			wide 60°		
h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)
1	939.1	o0.35	1	1566	o1.07
2	234.7	o0.69	2	391.4	o1.94
3	104.3	o1.02	3	174.0	o2.81
4	58.7.1	o1.36	4	97.88	o3.68
5	37.5.6	o1.69	5	62.64	o4.55

Accessories

- 2  Glass Diffuser
- 2  Honeycomb Louvre