



# Commercial Office 210

 IP65


 Class III


 Ceiling Recessed

 Acoustic Proof

 Anti glare hazard  
UGR<9

 RG1 | Blue light

 165mm

 Altamente riciclabile  
Highly recyclable


 FSC  
Package





## 25.2Watt Deep Recessed Low Glare Downlight


Code	System Power	LED Power	Lumens(at 3000K)	CRI	Lifetime (Ta 25°C)
DL3541	28.3W	700mA 36V	2245lm	>93	50.000h L90B10

Finish	Baffle Finishes	LED CCT	Beam	Key Information	
<input type="checkbox"/> 101 Textured White	<input type="checkbox"/> 201 Matt White	<input type="checkbox"/> 2700K	<input type="checkbox"/> 20°	Material	Aluminium
<input type="checkbox"/> 102 Textured Black	<input type="checkbox"/> 202 Matt Black	<input type="checkbox"/> 3000K	<input type="checkbox"/> 40°	Mounting	Ceiling Recessed
		<input type="checkbox"/> 4000K	<input type="checkbox"/> 60°	Gear	This product is supplied without gear.
				Warranty	5 Year

 165-210mm



 165mm



### Light Distribution for 3000K

wide 57°

h(m)	E(lx)	o(m)
1	2717	o1.08
2	679.3	o2.16
3	304.3	o3.24
4	169.8	o4.32
5	108.7	o5.40

### Accessories

2  Glass Diffuser

2  Honeycomb Louvre