















Commercial Tilt 140


-  IP21
-  Class III
-  Ceiling Recessed
-  Anti glare hazard UGR<14
-  RG1 | Blue light
-  140mm
-  Altamente riciclabile Highly recyclable
-  FSC Package



25.2Watt Gimble Tiltable Downlight

Code	System Power	LED Power	Lumens(at 3000K)	CRI	Lifetime (Ta 25°C)
DL3564	28.3W	700mA 36V	2650lm	>93	50.000h L90B10



Finish	Baffle Finishes	LED CCT	Beam	Key Information
<input type="checkbox"/> 101 Textured White	<input type="checkbox"/> 201 Matt White	<input type="checkbox"/> 2700K	 15°	Material Aluminium
<input type="checkbox"/> 102 Textured Black	<input type="checkbox"/> 202 Matt Black	<input type="checkbox"/> 3000K	 24°	Mounting Ceiling Recessed
		<input type="checkbox"/> 4000K	 36°	Gear This product is supplied without gear.
		 D2W	 50°	Warranty 5 Year
		 TW		



Light Distribution for 3000K

medium 40°			wide 50.5°		
h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)
1	3757	o0.74	1	2421	o0.95
2	939.3	o1.47	2	605.3	o1.90
3	417.5	o2.21	3	269.0	o2.86
4	234.8	o2.95	4	151.3	o3.81
5	150.3	o3.69	5	96.85	o4.77

Accessories

- 2  Glass Diffuser
- 2  Honeycomb Louvre