

LV Track Circular 300


-  IP21
-  Class III
-  48V Track
-  Anti glare hazard UGR<19
-  RG1 | Blue light
-  Altamente riciclabile Highly recyclable
-  FSC Package



18Watt Wall Circular Diffused Downlight for Low Voltage Track

| Code | System Power | LED Power | Lumens(at 3000K) | CRI | Lifetime (Ta 25°C) |
|--------|--------------|-----------|------------------|-----|--------------------|
| TR3102 | 20.6W | 500mA 36V | 1400lm | >90 | 50.000h L90B10 |

| Finish | LED CCT | Beam | Key Information | |
|--------------------|---------|------|-----------------|-----------|
| 101 Textured White | 2700K | 20° | Material | Aluminium |
| 102 Textured Black | 3000K | 30° | Mounting | 48V Track |
| | 4000K | 40° | Warranty | 5 Year |



Light Distribution for 3000K

| spot 21° | | | medium 26° | | | wide 38° | | |
|----------|-------|-------|------------|-------|-------|----------|-------|-------|
| h(m) | E(lx) | o(m) | h(m) | E(lx) | o(m) | h(m) | E(lx) | o(m) |
| 1 | 2172 | o0.37 | 1 | 2478 | o0.47 | 1 | 1498 | o0.68 |
| 2 | 543.1 | o0.75 | 2 | 619.5 | o0.94 | 2 | 374.5 | o1.36 |
| 3 | 241.4 | o1.12 | 3 | 275.3 | o1.40 | 3 | 166.4 | o2.04 |
| 4 | 135.8 | o1.49 | 4 | 154.9 | o1.87 | 4 | 93.62 | o2.72 |
| 5 | 86.90 | o1.87 | 5 | 99.12 | o2.34 | 5 | 59.92 | o3.41 |

Gear

This product is supplied with 48V on/off, DALI track adaptor.