






Display Swivel 52


-  IP21
-  Class III
-  Ceiling Recessed
-  RG1 | Blue light
-  52mm
-  Altamente riciclabile
Highly recyclable
-  FSC
Package



2.1Watt Mini Spot for Cabinet or Ceiling

Code	System Power	LED Power	Lumens(at 3000K)	CRI	Lifetime (Ta 25°C)
DL3331	3W	700mA 3V	150lm	≥90	50.000h L90B10

Finish	LED CCT	Beam	Key Information	
101 Textured White	2700K	24°	Material	Aluminium
102 Textured Black	3000K	36°	Mounting	Ceiling Recessed
	4000K	50°	Gear	This product is supplied without gear.
			Warranty	5 Year



Light Distribution for 2700K

spot 18°			medium 24°			wide 34°		
h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)
1	551.1	ø0.32	1	402.4	ø0.44	1	276.0	ø0.60
2	137.8	ø0.65	2	100.6	ø0.88	2	69.00	ø1.22
3	61.23	ø0.97	3	44.71	ø1.31	3	30.67	ø1.83
4	34.44	ø1.30	4	25.15	ø1.75	4	17.25	ø2.43
5	22.04	ø1.62	5	16.09	ø2.19	5	11.04	ø3.04