

**DL3367**

**3W mini size gimble tiltable under shelf light**



**Description**

Downlight for indoor use.




Compact size; Delicate design; Short and long snoot version available; Precise light direction control; Suitable for use as under-cabinet/shelf, reading, and other focused luminaries;

**Finish**

Black  
White

**Material**

Aluminium  
PMMA



→ Cutout:35mm  
▨ 5-25mm

**TECHNICAL CHARACTERISTICS**

**Light source**

Light source: Luminus SST20 Chip  
Output (W): 700mA 3V 3W  
Total power consumption (W): 3  
Color temperature: 2700K, 3000K, 4000K  
CRI:  $\geq 90$   
Photobiological risk: RG1  
Real Lumen: 140  
Qty Leds: 1  
Lm/Real W: 70  
Life Time: 50.000h L90B20  
MacAdam steps: 3  
UGR: 24(Short snoot); 13(Long snoot)

**GEAR**

This item requires gear.  
It is not included.  
  
Recommended gears:  
HEP LSC4W700P UNI

**Logistics**

Net Weight (Kg): 0.18  
Weight in Kg (packaged): 5  
Packing: 36.5 x 35.5 x 34  
Masterbox: 100

**Luminaire**

IP20 suitable for indoor use only  
crossing: No  
Warranty: 5 Years

**LIGHT DISTRIBUTION for 2700K spot 18°**

h(m)	E(lx)	Ø(m)
1	551.1	Ø0.32
2	137.8	Ø0.65
3	61.23	Ø0.97
4	34.44	Ø1.30
5	22.04	Ø1.62

Photometric 2700K 18D Ra.90

**LIGHT DISTRIBUTION for 2700K medium 24°**

h(m)	E(lx)	Ø(m)
1	402.4	Ø0.44
2	100.6	Ø0.88
3	44.71	Ø1.31
4	25.15	Ø1.75
5	16.09	Ø2.19

Photometric 2700K 24D Ra.90



The photograph may not match the reference exactly. Please read the product description to identify the finish.