


**WL3185 Eyelid, WL3185 Diffused**

**2W 24V Surface Mount LED Marker**



**Description**

24V constant voltage dimming;  
Supplied with eyelid & diffused versions;  
Ultra slim and compact body;  
IP65;

**Finish**

Black/White

**Material**

Aluminium



**TECHNICAL CHARACTERISTICS**

**Light source**


Light source: SMD LED 2835  
Output (W): 1.5W  
Total power consumption (W): 24V, 2W  
Color temperature: 2700K/3000K/4000K  
CRI: 90  
Photobiological risk: RG1  
Real Lumen: 45.34lm  
Qty Leds: 1  
Lm/Real W: 23lm/w  
Life Time: 50.000h L80B20  
MacAdam steps: 3  
UGR: <19

**GEAR**

This product is supplied without gear;

**Luminaire**

This product is designed for indoor&outdoor use.  
Crossing: No  
Warranty: 5 Years



**PHOTOMETRIC DATA**

LIGHT DISTRIBUTION for 3000K  
110 Deg

h(m)	E(lx)	Ø(m)
1	16.38	Ø2.91
2	4.09	Ø5.82
3	1.82	Ø8.74
4	1.02	Ø11.65
5	0.65	Ø14.57

The photograph may not match the reference exactly. Please read the product description to identify the finish.