

Classic Tilt 75

IP21

Class III

Ceiling Recessed

Anti glare hazard
UGR<19

RG1 | Blue light

75mm

Altamente riciclabile
Highly recyclable


FSC
Package



9Watt Deep Tilttable Downlight

Code	System Power	LED Power	Lumens(at 3000K)	CRI	Lifetime (Ta 25°C)
DL3854	11W	250mA 36V	855lm	93/97	50.000h L90B20

Finish	LED CCT	Beam	Key Information	
Powder Coat	2700K	15°	Material	Aluminium
Liquid Paint	3000K	24°	Mounting	Ceiling Recessed
Anodize	4000K	38°	Gear	This product is supplied without gear.
Plate	D2W	60°	Warranty	5 Year
	TW			



Light Distribution for 2700K

narrow 24°			medium 38°			wide 60°		
h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)
1	2268	ø0.49	1	1407	ø0.71	1	936.2	ø1.14
2	567.1	ø0.98	2	351.7	ø1.43	2	234.0	ø2.29
3	252.0	ø1.48	3	156.3	ø2.15	3	104.0	ø3.44
4	141.8	ø1.97	4	87.92	ø2.86	4	58.51	ø4.59
5	90.73	ø2.46	5	56.27	ø3.58	5	37.45	ø5.74

Accessories

2 Glass Diffuser

2 Honeycomb Louvre