

DL3854

10W Round Tiltable Recessed Downlight

Description

Modulized;
Low glare reflector;
Interchangeable reflectors with different beam angles;
Suitable for concrete installation;

Finish

Black/White
Light Bronze/Dark Bronze/Brushed Varnish

Material

Aluminium



TECHNICAL CHARACTERISTICS

Light source

Light source: Citizen CLU02Q-1202
Output (W): 9W (250mA 36V)
Total power consumption (W): 10W
Color temperature: 2700K/3000K/4000K
CRI: 90
Photobiological risk: RG1
Real Lumen: 809lm
Qty Leds: 1pc
Lm/Real W: Min.80
Life Time: 50.000h L80B20
MacAdam steps: 2
UGR: <19

Gear

This product is supplied without gear.

Luminaire

Crossing: No
Warranty: 5 Years

LIGHT DISTRIBUTION for 2700K Narrow 24°


h(m)	E(lx)	Ø(m)
1	2268	Ø0.49
2	567.1	Ø0.98
3	252	Ø1.48
4	141.8	Ø1.97
5	90.73	Ø2.46

LIGHT DISTRIBUTION for 2700K Medium 38°

h(m)	E(lx)	Ø(m)
1	1407	Ø0.71
2	351.7	Ø1.43
3	156.3	Ø2.15
4	87.92	Ø2.86
5	56.27	Ø3.58

LIGHT DISTRIBUTION for 2700K Wide 60°

h(m)	E(lx)	Ø(m)
1	936.2	Ø1.14
2	234	Ø2.29
3	104	Ø3.44
4	58.51	Ø4.59
5	37.45	Ø5.74



The photograph may not match the reference exactly. Please read the product description to identify the finish.