

# Classic Trimless Fix 75



IP44



Class III



Ceiling Recessed



Acoustic Proof



Anti glare hazard  
UGR<19



RG1 | Blue light



90mm



Altamente riciclabile  
Highly recyclable




FSC  
Package



## 9Watt Fixed Deep Trimless Downlight

| Code   | System Power | LED Power | Lumens(at 3000K) | CRI   | Lifetime (Ta 25°C) |
|--------|--------------|-----------|------------------|-------|--------------------|
| DL3979 | 11W          | 250mA 36V | 900lm            | 93/97 | 50.000h L90B20     |

| Finish       | LED CCT | Beam | Key Information |                                        |
|--------------|---------|------|-----------------|----------------------------------------|
| Powder Coat  | 2700K   | 15°  | Material        | Aluminium                              |
| Liquid Paint | 3000K   | 24°  | Mounting        | Ceiling Recessed                       |
| Anodize      | 4000K   | 38°  | Gear            | This product is supplied without gear. |
| Plate        | D2W     | 60°  | Warranty        | 5 Year                                 |
|              | TW      |      |                 |                                        |



### Light Distribution for 2700K

| narrow 24° |       |       | medium 38° |       |       | wide 60° |       |       |
|------------|-------|-------|------------|-------|-------|----------|-------|-------|
| h(m)       | E(lx) | o(m)  | h(m)       | E(lx) | o(m)  | h(m)     | E(lx) | o(m)  |
| 1          | 2268  | ø0.49 | 1          | 1407  | ø0.71 | 1        | 936.2 | ø1.14 |
| 2          | 567.1 | ø0.98 | 2          | 351.7 | ø1.43 | 2        | 234.0 | ø2.29 |
| 3          | 252.0 | ø1.48 | 3          | 156.3 | ø2.15 | 3        | 104.0 | ø3.44 |
| 4          | 141.8 | ø1.97 | 4          | 87.92 | ø2.86 | 4        | 58.51 | ø4.59 |
| 5          | 90.73 | ø2.46 | 5          | 56.27 | ø3.58 | 5        | 37.45 | ø5.74 |

### Accessories

2 Glass Diffuser

2 Honeycomb Louvre