



DL3145

15W Semi Recessed Downlight

Description

Semi Design;
Easy maintenance;
Low-glare;

Finish

Black/White/Anodizing

Material

Aluminium



15D

24D

60D

TECHNICAL CHARACTERISTICS

Light source

Light source: Citizen CLU02Q-1202 350mA 36V

Output (W): 12.6W (350mA, 36V)

Total power consumption (W): 15W

Color temperature: 2700K/3000K/4000K

CRI: 90

Photobiological risk: RG1

Real Lumen: 1200lm (15W, 60D, 3000K, Ra.90)

Qty Leds: 1

Lm/Real W: 80

Life Time: 50.000h L90B10

MacAdam steps: 3

UGR: <19

Gear

This product is supplied without gear

With Sunricher Dali led driver

SRP-2305N-15CC100 -700 6- 42VDC 100-700(Via NFC)15W

With honeycomb louvre

Luminaire

Downlight suitable for indoor area

crossing: No

Warranty: 5 Years

LIGHT DISTRIBUTION for 3000K

Wide 60°

h(m)	E(lx)	Ø(m)
1	1353	Ø1.06
2	338.2	Ø2.13
3	150.3	Ø3.20
4	84.33	Ø4.27
5	54.11	Ø5.33

The photograph may not match the reference exactly. Please read the product description to identify the finish.