

Product Description: 5W Semi Mini Recessed Downlight
Model: DL3298



IP54   

Technical Data

Light source	Luminus CXM-3
System wattage	5W (120mA, 36V)
Lumen flux	250lm (5W, 24D, 2700K, Ra.90)
Colour temperature	2700K, 3000K, 4000K
Colour rendering index	Ra≥90
Chromaticity rate	3 MacAdam
Beam angle	15D, 24D, 36D, Lens Type
Service lifetime	50,000hrs, L70
Ingress protection	IP54 Installed
Operation voltage	220-240Vac, 50/60Hz
Operation temperature	-20~40D
Protection class	III
Finishing	White RAL9003, Gloss 5 Black RAL9005, Gloss 5
Construction	Aluminum
Mounting	Ceiling Recessed, spring type
Warranty	5 years
Lighting control	Actec non-dim, ECG standard Actec triac dim 0-10V, Dali diming upon request

Ordering Data

DL3298					
Model	Finish	Power	CCT	CRI	Beam
	• AW	• 5	• 27	• R90	• 15D
	• AB		• 30		• 24D
	• CH		• 40		• 36D
	• RG				

Features

- Compact size
- High lux intensity
- Higher power

Accessories

- N/A

Diagram



LIGHT DISTRIBUTION for 2700K medium 19°

h(m)	E(lx)	Ø(m)
1	148.7	Ø0.33
2	37.18	Ø0.66
3	16.52	Ø1.00
4	9.294	Ø1.33
5	5.948	Ø1.66

Photometric 2700K 24D Ra.90