

WL3351

3W Surface Mounted LED Reading Light

Description

1 formats and 2 models(with black lit, without); Equipped with USB-A and USB-C ports; One driver for all functionalities; 3 step dimming on both spots and black lit;

Finish Black/White/Bronze **Material** Aluminium



TECHNICAL CHARACTERISTICS

Light source

Light source: Citizen CLU7L3 Output (W): 2.1W(700mA 3V) Total power consumption (W): 3W Color temperature: 2700K/3000/4000K CRI: ≥90 Real Lumen: 120LM Lm/Real W: 40 Life Time: 50.000h L70 B20 MacAdam steps: 3 UGR: N/A

GEAR

This product is suppled with gear One driver for all: by using Meanwell APV-25-5 constant voltage driver(Max.3.5A)


Luminaire

IP20 for indoor use crossing: No Warranty: 5 Years

The photograph may not match the reference exactly. Please read the product description to identify the finish.







WL3352

3W Surface Mounted LED Reading Light

Description

1 formats and 2 models(with black lit, without); Equipped with USB-A and USB-C ports; One driver for all functionalities; 3 step dimming on both spots and black lit; All model shares the same concept/size/back plate/driver/control board; Difference between with/without back lit is just the aluminum sheet in 6mm

Finish

Black/White/Bronze

Material Aluminium



TECHNICAL CHARACTERISTICS

Light source

Light source: Citizen CLU7L3 Output (W): 2.1W(700mA 3V) Total power consumption (W): 3W Color temperature: 2700K/3000/4000K CRI: ≥90 Real Lumen: 120LM Lm/Real W: 40 Life Time: 50.000h L70 B20 MacAdam steps: 3 UGR: N/A

GEAR

This product is suppied with gear One driver for all: by using Meanwell APV-25-5 constant voltage driver(Max.3.5A)


Luminaire

IP20 for indoor use crossing: No Warranty: 5 Years

The photograph may not match the reference exactly. Please read the product description to identify the finish.







WL3353

3W Surface Mounted LED Reading Light

Description

1 formats and 2 models(with black lit, without); Equipped with USB-A and USB-C ports; One driver for all functionalities; 3 step dimming on both spots and black lit; All model shares the same concept/size/back plate/driver/control board; Difference between with/without back lit is just the aluminum sheet in 6mm

Fin	isł	ı		

Black/White/Bronze

Material Aluminium



TECHNICAL CHARACTERISTICS

Light source

Light source: Osram SSL150 Output (W): 2.1W(700mA 3V) Total power consumption (W): 3W Color temperature: 2700K/3000/4000K CRI: ≥90 Real Lumen: 120LM Lm/Real W: 40 Life Time: 50.000h L70 B20 MacAdam steps: 3 UGR: N/A

GEAR

This product is suppied with gear One driver for all: by using Meanwell APV-25-5 constant voltage driver(Max.3.5A)

Luminaire

IP20 for indoor use crossing: No Warranty: 5 Years

The photograph may not match the reference exactly. Please read the product description to identify the finish.