



The photograph may not match the reference exactly. Please read the product description to identify the finish.

WL3399

2*5W Up&Down wall light

Description

For outdoor use;
Non dim/Triac dimmable driver;
Built-in driver.

Finish

White/Black
Dark Bronze/Light Bronze

Material

Aluminium



36D

40D

TECHNICAL CHARACTERISTICS

Light source

Light source: Citizen CLU02Q-1202 chip
Output (W): 2*5W (2*130MA 36V)
Total power consumption (W): 10W
Color temperature: 2700K/3000K/4000K
CRI: ≥90
Photobiological risk: RG1
Real Lumen: 298.18 lm(2700K 36D)
Qty Leds: 2
Lm/Real W: 27.88
Life Time: 50.000h L90B10
MacAdam steps: 3
UGR: <14

GEAR

This product is supplied with gear.
With Built-in ACTEC Triac dimmable driver
MINI-10-260T 260mA 20-39V

Luminaire

IP65 for outdoor using
crossing: No
Warranty: 5 Years

LIGHT DISTRIBUTION for 2700K Narrow 36°

h(m)	E(lx)	Ø(m)
1	20.27	Ø3.61
2	5.068	Ø7.23
3	2.253	Ø10.8
4	1.267	Ø14.4
5	0.810	Ø18.1

LIGHT DISTRIBUTION for 2700K Narrow 40°

h(m)	E(lx)	Ø(m)
1	9.598	Ø1.94
2	2.399	Ø3.88
3	1.066	Ø5.83
4	0.599	Ø7.77
5	0.383	Ø9.72