










# Classic Dual Color 75


-  IP44
-  Class III
-  Ceiling Recessed
-  Acoustic Proof
-  Anti glare hazard UGR<19
-  RG1 | Blue light
-  75mm
-  Altamente riciclabile Highly recyclable
-  FSC Package



## New 9Watt Deep Fixed Downlight with Intchangeable Bezel

Code	System Power	LED Power	Lumens(at 3000K)	CRI	Lifetime (Ta 25°C)
DL6308	11W	250mA 36V	900lm	93/97	50.000h L90B20



Finish	LED CCT	Beam	Key Information	
Powder Coat	 2700K	 15°	Material	Aluminium
Liquid Paint	 3000K	 24°	Mounting	Ceiling Recessed
Anodize	 4000K	 38°	Gear	This product is supplied without gear.
Plate	 D2W	 60°	Warranty	5 Year
	 TW			



### Light Distribution for 2700K

narrow 24°			medium 38°			wide 60°		
h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)	h(m)	E(lx)	o(m)
1	2268	o0.49	1	1407	o0.71	1	936.2	o1.14
2	567.1	o0.98	2	351.7	o1.43	2	234.0	o2.29
3	252.0	o1.48	3	156.3	o2.15	3	104.0	o3.44
4	141.8	o1.97	4	87.92	o2.86	4	58.51	o4.59
5	90.73	o2.46	5	56.27	o3.58	5	37.45	o5.74

### Accessories

- 2  Glass Diffuser
- 2  Honeycomb Louvre