
















# Square 9 Spots Surface

-  IP21
-  Class I
-  Ceiling Surface
-  Anti glare hazard  
UGR<17
-  RG1 | Blue light
-  Altamente riciclabile  
Highly recyclable
-  FSC  
Package




## New 20Watt 9Heads 3\*3 Surface Mounted Spot

| Code   | System Power | LED Power | Lumens(at 3000K) | CRI | Lifetime (Ta 25°C) |
|--------|--------------|-----------|------------------|-----|--------------------|
| SD3361 | 18W          | 500mA 36V | 2100lm           | ≥90 | 50.000h L90B10     |

| Finish                                                                         | LED CCT                                                                                   | Beam                                                                                    |
|--------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| <span style="border: 1px solid black; padding: 2px;">101</span> Textured White |  2700K |  15° |
| <span style="border: 1px solid black; padding: 2px;">102</span> Textured Black |  3000K |  24° |
|                                                                                |  4000K |  36° |
|                                                                                |                                                                                           |  55° |
|                                                                                |                                                                                           |  75° |

| Key Information |                        |
|-----------------|------------------------|
| Material        | Press steel, aluminium |
| Mounting        | Ceiling Surface        |
| Warranty        | 5 Year                 |



### Light Distribution for 3000K

middle 36°

| h(m) | E(lx) | o(m)  |
|------|-------|-------|
| 1    | 4881  | o0.59 |
| 2    | 1220  | o1.18 |
| 3    | 542.4 | o1.77 |
| 4    | 305.1 | o2.36 |
| 5    | 195.2 | o2.96 |

### Gear

This product is supplied with triac dim driver or DALI driver.